

[Click Here](#)



Models/Modelos/Modèles 468-SD-DST, 16926-SD-DST, 16927-SD-DST, 16929-SD-DST & 16932-SD-DST Series/Series/Seria Write purchased model number here. Escriba aquí el número del modelo comprado. Inscrivez le numéro de modèle ici. WARNING: THIS FAUCET IS NOT TO BE USED WITH PORTABLE DISHWASHERS! / ADVERTENCIA: ¡SESTA LLAVE NO SE DEBE UTILIZAR CON MAQUINAS LAVAPLATOS PORTATILES! / AVERTISSEMENT: ON NE DOIT PAS BRANCHER UN LAVE-VAISSELE PORTATIF SUR CE ROBINET! For easy installation of your Delta faucet you will need: • To READ ALL the instructions completely before beginning. • To READ ALL warnings, care, and maintenance information. Para instalación fácil de su llave Delta usted necesitará: • LEER TODAS las instrucciones completamente antes de empujar. • LEER TODOS los avisos, cuidados, e información de mantenimiento. Pour installer votre robinet Delta facilement, vous devez: • LIRE TOUTES les instructions avant de débiter; • LIRE TOUS les avertissements ainsi que toutes les instructions de nettoyage et d'entretien. SINGLE HANDLE PULL/OUT KESSLER 73040 LEWISTON LLAVES EXTRIBLES DE AGUA PARA COCINAS KESSLER ROBINETS A UNE MANETTE À BEC-DOUCHETTE RÉTRACTABLE KESSLER ET CICERO 1 AND CICERO KITCHEN FAUCETS @ @ DEBONAIR LEWISTON™ @ DEBONAIR™ POUR EVIERS DE CUISINE @ You may need/Usede puede necesitar/ Articles dont vous pouvez avoir besoin: DEBONAIR™ Y CICERO @ @ LEWISTON @ 1/8" 8/27/15, @ @ Rev. B Delta@ faucets with DIAMOND™ Seal Technology perform like new for life with a patented design which reduces leak points, is less hassle to install and lasts twice as long as the industry standard*. Kitchen faucets with Touch-Clean® Spray Holes allow you to easily wipe away calcium and lime build-up with the touch of a finger. You can install with confidence, knowing that Delta faucets are backed by our Lifetime Limited Warranty. *Industry standard is based on ASME A112.18.1 of 500,000 cycles. Timeless design for today's homes! Pull-out spout operates in an aerated or spray mode with an easy push button! Includes optional matching soap or lotion dispenser! Optional 10 1/2" escutcheon included Technology and Special Features ADA Compliant Some people, and some local codes, require fixtures that are compliant with the Americans with Disabilities Act. If someone may visit who has special needs, or if you believe future buyers might appreciate this feature, Delta offers a range of compliant fixtures. Touch-Clean® Rubber spray holes allows easy cleaning with the touch of a finger. No-Lead Compliant Compliant with State and Federal drinking water legislation. Brilliance® Finish Many Delta products are made with Brilliance® finishes, which resist abrasions and discolorations better than traditional brass or even chrome. Water-Efficient CalGreenCert Tooltip information here... Soap Dispenser A soap/lotion dispenser coordinates with the look of your kitchen, and loads conveniently from the top. You won't need to keep a bottle of liquid soap or lotion on your counter. Diamond Seal® Technology DIAMOND™ Seal Technology is Delta's revolutionary new water delivery system. An internal contact surface made up of tiny diamonds makes the valve leak-free and extraordinarily durable. It also keeps water free of contact with potential metal contaminants. Need help with installation? Mike & Hannah are here to help! Get advice from the pros on everything from installation to product care. PART LIST View Product Delta@ Escutcheon - Pull-Out List Price: \$20.45 - \$27.05 RP51490 View Product Delta@ O-Ring List Price: \$7.60 Online Price: \$5.80 RP13938 4.50 2 View Product DELTA Handle Assembly List Price: \$53.60 - \$59.15 RP73043SS View Product Victorian@ Aerator & Wrench - Pull-Out or Pull-Down List Price: \$28.65 Online Price: \$21.84 RP50815 4.54 26 View Product Delta@ Soap / Lotion Dispenser - Nut List Price: \$7.65 Online Price: \$5.84 RP21945 3.00 1 View Product Delta@ Bonnet Cap List Price: \$16.65 - \$45.80 RP51502 View Product Valdosta@ Escutcheon - 3 Hole - Pull-Out Kitchen List Price: \$33.40 - \$78.40 RP44645 View Product Delta@ Set Screw List Price: \$9.65 Online Price: \$7.36 RP152 4.20 5 View Product Delta@ Bonnet Nut w/ Valve Seal List Price: \$32.35 Online Price: \$24.64 RP51503 5.00 3 View Product Palo@ O-Ring - Pull-Out List Price: \$12.55 Online Price: \$9.56 RP44648 View Product Delta@ Mounting Nut, Washer & Screws (2) List Price: \$39.45 Online Price: \$30.04 RP49835 View Product Delta@ Cartridge - DIAMOND™ Valve - 1H List Price: \$71.05 Online Price: \$47.36 RP50587 2.91 207 Rated 5 out of 5 by amandascheid02_2453 from Love! It We recently remodeled our master bathroom and this is the faucet we installed! We absolutely love it and goes perfect r with pur decor! Definitely recommend this brand! Date published: 2025-02-20 Rated 5 out of 5 by laceey17_5009 from An amazing faux I received this sink for free from influencer for my honest opinion honestly, honestly I haven't been able to switch my faucet yet it looks very nice and I can't wait to do it. I read the instructions and it seems really easy. Durability and function seems great. My water pressure is off but that's because of my own pipes. I can't wait to be able to install this faucet in my sink. Date published: 2025-01-24 Rated 5 out of 5 by floundering_ardr 7041 from Looks really nice I received this product complimentary as part of my voxbox. I'm having my sink replaced first so the faucet hasn't been installed yet. But the product looks very nice and feels sturdy. The directions appear straight forward as well. Date published: 2025-01-17 Rated 5 out of 5 by stephanier04_4058 from Beautiful upgrade Our faucets are all really outdated. This was much needed. It's amazing what just changing a faucet can do for your space! The instructions were very basic, so you definitely want to know what you're doing. Came with everything you would need in the mounting application. We had a little bit of an issue getting it to set right. But my fiance is a retired plumber, and he just got ahead of himself trying to go to fast. Once we took it apart and put it back together it fit perfectly. I love the pull down sprayer, it has a little button to turn the sprayer on/off underneath. But you can also just pull and spray with a steady flow of water. The bottle is pretty easy to refill with soap. We love delta! Date published: 2025-01-06 Rated 1 out of 5 by Shutoff from Faucet Won't Shutoff Worked great for about a year then was hard to shutoff. Very difficult to shutoff. Date published: 2024-12-11 Rated 3 out of 5 by kendrat49_2995 from Good The instructions were super easy to follow. It took about an hour for me to change my old one out. This was very nice once put in. The soap dispenser is a nice touch also. Date published: 2024-12-03 Rated 5 out of 5 by alexandrea2_92725 from Great product Functionality of this product is easy and straight forward, installation was super easy. It has great water pressure, is durable and has an amazing design. Date published: 2024-11-19 Rated 5 out of 5 by Anonymous from Perfect replacement. I would highly recommend this to anyone looking for a nice smooth working faucet, it has everything I need in a faucet and looks like it will last for a long time. Quality purchase at a reasonable price point. Date published: 2024-11-16 Asked by: jrwrgby5f HI, jrwrgby5f! Thank you for your question. The Delta 16932-SSSD-DST Faucet will not have 'Kessler' Stamped on the faucet. It will have 'Delta' stamped on there, which all of our current Delta Faucets have our Delta name stamped on the faucet, as well. Best Regards, Rosanna Answered by: Delta Faucet Date published: 2024-03-28 Asked by: Marianna Thank you for your question, Marianna! Yes, model 16932-SSSD-DST can be swiveled from left to right. Best Regards, Benjamin Answered by: Delta Faucet Date published: 2024-05-27 Asked by: Karen Hello Karen! Thank you for your question. The part number for the replacement sprayer is rp7304 (in stainless steel). Thanks, Antoine Answered by: DeltaFaucet Date published: 2024-03-28 Asked by: Tracey Thank you for your question, Tracey! The optional escutcheon plate included with model 16932-SSSD-DST includes a gasket. If this was discarded, however, a thin bead of Silicone can be used instead. 20Rev*920A.pdf Best regards, Edward Answered by: Delta Faucet Date published: 2024-03-28 Asked by: Scott Thank you for your question, Scott! We do not recommend attaching a portable dishwasher to a pull-out/pull down model as the pressure is likely to cause a leak or internal damage to the faucet. Best regards, Edward Answered by: Delta Faucet Date published: 2024-03-28 Asked by: Sandy Hi, Sandy! Thank you for your question. The Delta 16932-SSSD-DST Faucet hose assembly is part number RP50390. Here is a link to the hose: Best Regards, Rosanna Answered by: Delta Faucet Date published: 2024-03-28 Asked by: Bill Hi Bill, Thank you for your question. The aerator for the 16932-SD-DST faucet is available to order separately as RP50815. Thanks, Dave Answered by: DeltaFaucet Date published: 2024-03-28 Asked by: Robert This online price is exclusive to DeltaFaucet.com. The list price may be shown on products offered outside of the Outlet section on DeltaFaucet.com. Strikethrough pricing may be used to show discounts. Share — copy and redistribute the material in any medium or format for any purpose, even commercially. Adapt — remix, transform, and build upon the material for any purpose, even commercially. The licensor cannot revoke these freedoms as long as you follow the license terms. Attribution — You must give appropriate credit , provide a link to the license, and indicate if changes were made . You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use. ShareAlike — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. No additional restrictions — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits. You do not have to comply with the license for elements of the material in the public domain or where your use is applicable exception or limitation . No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material. So you bought your dream faucet, and now you need to install it? Piece of cake. If you can turn off the water, you can install a single-handle pull-down kitchen faucet in mere minutes. Here's how. What you'll need: Screwdriver Adjustable wrench Allen wrench Flow How to install it: 1. Turn off the sink's water supply. If necessary, remove the old faucet. 2. Feed the flexible spray hose through the faucet's spout—be sure you guide it in the right direction—and then through the hub. 3. Align the hole in the back of the spout with the clip on the hub, and work it in with a back-and-forth motion until it snaps into place. 4. Attach the sprayer to the end of the hose, and tighten the connection by hand. Delta MagnaTite Docking will keep the sprayer firmly in place while you work. 5. Depending on your countertop's material and thickness, you may need an escutcheon and gasket to mount your faucet (get them here, if it's not included in the box). 6. Insert the faucet through the mounting hole in the countertop. 7. Under the sink, slide the U-shaped mounting bracket over the faucet shank; the supply lines should fit inside the bracket. Screw the nut onto the end of the shank, and use the Allen wrench to tighten the nut against the underside of the counter. Make sure the faucet is properly positioned over the sink before you tighten it for good. 8. Slide the hose weight over the hose, then push the hose's end securely onto the faucet outlet. Place the clip over the connection to hold it in place. 9. Attach the water supply lines. Look at the ends of each line: A blue tip denotes the cold water line; red marks the hot water. Run each line to its corresponding water supply; the 3/8-inch compression fitting at the end should fit directly onto the water supply valve (if it doesn't fit, you'll need an adapter). If the lines are too long, wind them into a loop at least 8 inches in diameter, being careful not to create a kink in the lines. Screw the lines on by hand, then tighten snugly with the adjustable wrench; one wrench turn past finger-tight should be tight enough. 10. Open the faucet handle to "full on," then turn on the water supply. Let the water run 30 to 40 seconds to remove any debris in the lines. Shut the faucet off and check for leaks. (If you notice any leaks, tighten the connections another half turn with the wrench.) Register Online: www.deltafaucet.com/register To reference replacement parts and access additional technical documents and product info, visit www.deltafaucet.com 1-800-345-3358 Read all instructions prior to installation. CAUTION: Failure to read these instructions prior to installation may result in personal injury, property damage, or product failure. Manufacturer assumes no responsibility for product failure due to improper installation. WARNING: This faucet is not to be used with portable dishwashers. You may need Cleaning and Care Care should be given to the cleaning of this product. Although its finish is extremely durable, it can be damaged by harsh abrasives or polish. To clean, simply wipe gently with a damp cloth and blot dry with a soft towel. Note: ShieldSpray® not included with all models. Delta® ShieldSpray® Technology cuts through stubborn messes with a concentrated stream and contains the splatter with an innovative water shield. Now you can power off the mess without making a bigger one. SINGLE HOLE MOUNTING HARDWARE(S) (1), (2) & (3) Mounts above deck/sink and under the faucet hub. Be sure to align trim ring tabs (4) (if your faucet has a trim ring) in base of the hub. Thin Deck Aid RP37490 is not included with all models. Use to provide stiffness to thin gauge sinks. - To order, visit www.deltafaucet.com. Open your faucet package and determine what type of gasket (1) gasket & trim ring (2), or gasket, base ring & trim ring (3) plus mounting hardware and tools (5) that will be required to install your faucet based on the illustrations above compared to your supplied hardware. OPTIONAL Escutcheon Installation Not included with all models - To order, visit www.deltafaucet.com. For installations using the 10" escutcheon, be certain and use the 10" escutcheon (1) and under cover plate (2). Assemble under cover plate and escutcheon in place of single hole trim ring. Place the shanks (3) of the escutcheon/under cover plate assembly into the mounting holes of the sink. Slide the tubes and shank of the hub (4) through the escutcheon and mounting holes, then install hub onto escutcheon. Ensure that tabs (5) on escutcheon and plate are properly located in slots in bottom of hub. Mount as shown above using the nuts (6), bracket (7) and nut with wrench (8). Connection Standard Connections NOTICE To avoid risk of property damage, follow instructions for proper instation. Failure to follow these instructions may result in risk of property damage caused by leaking at this connection. Do not use pipe dope or other sealants on water line connections. Ensure all fittings and end connections are free of debris. Faucet fittings (1) are 3/8" compression. Loop tubing (2) if it is too long. Note: Recommended tubing minimum bend diameter is 8". Secure metal nut (3) to supply valve connection (4). Turn nut until it feels snug. Then tighten nut at least 2 more turns with a wrench. Repeat for other tube. Turn on water, examine for leaks. Custom Fit Connections NOTICE If you determine the PEX supply tubing for this faucet is too long and must be shorter to create an acceptable installation, be sure to read the instructions and plan ahead. When cutting the supply tubing the installer accepts the responsibility to do so in a way that allows a leak-free joint to be created. Delta is not responsible for tubing that is cut too short or cut in a way that will not allow for a leak-free joint. DO NOT use a metal sleeve (ferrule) or gasket (supplied with faucet) in place of the plastic sleeve (ferrule) supplied, it may not create a leak-free joint. Do not use pipe dope or other sealants on water line connections. For custom fit installations, you must use plastic sleeves (ferrules) supplied with model and nuts included on supply lines. Tube cut must be straight. Use plastic sleeve (ferrule) installation instructions found in and included in this document for more information. Slide nut (1) over plastic sleeve (ferrule) (3). Start nut by hand onto supply valve connection (2) to prevent cross-threading. Turn nut until it feels snug. Then tighten nut at least 2 more turns with a wrench. Repeat for other supply line. Turn on water, examine for leaks. Potential Problems and Remedies Tubing is not cut perpendicular to the axis of the tube: carefully make an additional cut, being careful not to cut the tube too short. Tubing is cut too short: buy a coupling union and a replacement supply line that mate together from a store. The coupling union end intended to connect to the faucet must mate to the standard 3/8" connection nuts and plastic sleeves (ferrules) supplied with the faucet. The plastic sleeve (ferrule) or connection nut is lost: purchase a replacement nut and/or plastic sleeve (ferrule) that are designed to seal with PEX tubing. Correct method NOTICE Failure to use plastic sleeve (ferrule) in the correct orientation will result in disconnection and possible water damage. Determine correct length of supply tube (1). Leave 1' or 2' of extra length to allow for easier installation and cut tube. Ensure cut is straight and burr free. Slide nut (2) and plastic sleeve (ferrule) (3) onto cut supply tube. Ensure plastic sleeve (ferrule) is oriented as shown. Insert supply tube into supply valve connection (4). Supply tube should touch bottom of hole inside supply valve. Slide plastic sleeve (ferrule) down supply tube until it contacts the supply valve connection. Slide nut over plastic sleeve (ferrule). Start nut by hand to prevent cross-threading. Turn nut until it feels snug. Then tighten nut at least 2 more turns with a wrench. Repeat for other supply line. Turn on water, examine for leaks. Incorrect installation Do not install sleeve upside down. Ensure cut is straight. Do not use gasket (1) supplied with PEX tubing or brass ferrule (2) supplied with valve stops. Ensure tube is fully inserted into stop before sliding sleeve down to engage top of fitting. Flush Supply Lines A. Place a bucket below outlet tube (1) and move the valve handle (2) to the open mixed position. Note: To turn on faucet, pull the lever away from the faucet. B. Then, while holding the outlet tube (1) over the bucket, slowly open and close the supply stops (3). This will prevent debris from being lodged in the hose and sprayer. C. Move faucet handle (2) to the off position, and carefully remove container of water. Hose Installation A. Insert hose end (1) through hose weight assembly (2). B. Push hose end (1) onto faucet outlet (3). Attach clip (4) over hose and outlet as shown. Pull down moderately to ensure connection has been made. B. Side View Setting The Handle Limit Stop (Optional) - not supplied with all models This faucet includes an integrated handle limit stop that has two positions. Position 1, to the left, allows full handle motion (the full range between "all cold" to "all hot"). The faucet is set in position 1 in the factory. Position 2, to the right, allows half of the normal handle motion ("all cold" to "mixed hot/cold"). Soap Dispenser Installation Note: Soap dispenser not included with all models. Remove nut (1). Separate head (2) from body (3). Insert body (3) and gasket (4) through selected hole in sink. Make sure gasket (4) is properly seated in the base. Secure body to sink with nut (1). From under the sink screw the bottle (5) onto the body assembly shank. Insert pump (6) into head (2), then drop into body (3). NOTE: To fill, lift the head and pump assembly out of the bottle and pour not more than 8 oz. into bottle. DO NOT remove bottle each time as this weakens the neck. Pull pump and head assembly out occasionally to soak and pump warm water through pump to remove soap build-up. Note: Initially it may take up to 12 pumps to bring soap to the pump tip. A. Turn on water supplies (1) and faucet valve handle (2). Check all connections at arrows for leaks. Refer back to the appropriate installation instructions and retighten if necessary. If assembled correctly, check for damage to seals and order appropriate replacements. B. Sprayer will lock into position when brought into proximity of the spout magnet. The sprayer can be removed by either pulling directly out from the spout or by twisting 90° in either direction which will cause the magnets to repel and the head to decouple from the spout (recommended). Check the operation of the 2 function sprayer by pushing the trigger (A) from aerator to spray. For models with a 3 function sprayer, check the operation by pushing the buttons to achieve the 3 different modes. Maintenance If faucet exhibits very low flow A. Remove and clean aerator (1) (Note: some models are not supplied with an aerator or a wrench is required (2) to remove aerator.). or B. Unscrew hose from spray head and clean debris from screen (the screen is located just inside the spray head (3). Note: Not all models have screens. IMPORTANT: Reinstall screen to the spray head or. (Failure to reinstall the screen could damage internal parts.) If faucet leaks from under handle: Remove handle (4) and cap (5). Using a wrench, ensure bonnet nut (6) is tight. If leak persists—SHUT OFF WATER SUPPLIES. Replace valve cartridge (7). When reinstalling parts, make sure bonnet nut (6) is tightened securely with a wrench.* WARNING: Failure to securely tighten bonnet nut with a wrench could result in water damage. Note: A small amount of water may run out the spout or drip for a very short period after the faucet is shut off. This is a natural occurrence caused by the long flexible hose. Note: Do not attempt to disassemble cartridge (7). There are no repairable parts inside. Maintenance If faucet exhibits very low flow - Unscrew hose from spray head and clean debris from screen (1) (the screen is located just inside the spray) - IMPORTANT: Reinstall screen to the spray head (failure to reinstall the screen could damage internal parts). If faucet leaks from under handle or from spout outlet - Insert a small screwdriver into slot (2) in button (3) and remove. Loosen set screw (4) inside of handle. Remove handle. Remove cap (5) by rotating counterclockwise. Bonnet may be stiff due to O-ring, but should rotate by hand. Remove bonnet nut (6) by rotating counterclockwise with a wrench. Remove cartridge (7) by pulling directly back on stem. Replace cartridge and reassemble. WARNING: Failure to securely tighten bonnet nut with a wrench could result in water damage. Note: A small amount of water may run out the spout or drip for a very short period after the faucet is shut off. This is a natural occurrence caused by the long flexible hose. 3 Function Wand Button 1 - Standard Flow Aerator Button 2 - 1.5 gpm at 60 psi Maximum Aerator Button 3 - Spray Mode Note - 3 Function Sprayer returns to position 2 if left in position 1 when the water is turned off. ShieldSpray® Models Button 1 - ShieldSpray Mode Button 2 - Spray Mode Button 3 - 1.8 gpm at 60 psi Maximum Aerator Note - 3 Function Sprayer returns to position 3 when button 1 is released. C. With the wand unlocked, press button 1 to use the ShieldSpray mode. Hold the plate 1/2 way through the bubble. For optimal performance, use in household with water pressure above 35 psi. The ShieldSpray feature may appear different at lower water pressures. Tip: Don't push the button while docked - always pull it close to the plate. Limited Warranty on Delta® Faucets Parts and Finish. All parts (other than electronic parts and batteries) and finishes of Delta® faucets purchased from authorized Delta sellers are warranted to the original consumer purchaser to be free from defects in material and workmanship for as long as the original consumer purchaser owns the home in which the faucet was first installed. For commercial purchasers, (a) the warranty period is ten (10) years for multi-family residential applications and (b) five (5) years for all other commercial applications, in each case from the date of original purchase. For purposes of this warranty, the term "multi-family residential application" refers to the purchase of the faucet from an authorized Delta seller by a purchaser who owns but does not live in the residential dwelling in which the faucet is initially installed, such as in a rented or leased single unit or multi-unit detached home (duplex or townhome), or a condominium, apartment building or community living center. The following installations are not considered multi-family residential applications, are excluded from the 10-year warranty and are subject to the 5-year warranty: industrial, institutional or other business premises, such as a dormitory, hospitality premises (hotel, motel or extended stay location), airport, educational facility, long- or short-term healthcare facility (hospital, rehabilitation center, nursing, assisted or staged-care living unit), public space or common area. Parts and Finish for Delta® Recertified Faucets. Delta Faucet Company offers for sale on deltafaucet.com Delta® Recertified faucets. All parts (other than electronic parts and batteries) and finishes of these Delta® Recertified faucets are warranted to the original consumer purchaser to be free from defects in material and workmanship for ten (10) years from the date of original purchase. For commercial purchasers, the warranty period is one (1) year from the date of original purchase. Electronic Parts. Electronic parts (other than batteries), if any, of Delta® faucets purchased from deltafaucet.com or authorized Delta sell-ers are warranted to the original consumer purchaser to be free from defects in material and workmanship for five (5) years from the date of original purchase or, for commercial purchasers, for one (1) year from the date of original purchase. No warranty is provided on batteries. What We Will Do. Delta Faucet Company will repair or replace, free of charge, during the applicable warranty period (as described above), any part or finish that proves defective in material and/or workmanship under normal installation, use and service. If repair or replacement is not practical, Delta Faucet Company may elect to refund the purchase price in exchange for the return of the product. These are your exclusive remedies. What Is Not Covered. Because Delta Faucet Company is unable to control the quality of Delta products sold by unauthorized sellers, unless otherwise prohibited by law, this warranty does not cover Delta products purchased from unauthorized sellers. Any labor charges incurred by the purchaser to repair, replace, install or remove this product are not covered by this warranty. Delta Faucet Company shall not be liable for any damage to the faucet resulting from reasonable wear and tear, outdoor use, misuse (including use of the product for an unintended application), freezing water, abuse, neglect or improper or incorrectly performed installation, maintenance or repair, including failure to follow the applicable care and cleaning instructions. Delta Faucet Company recommends using a professional plumber for all installation and repair of faucets. We also recommend that you use only genuine Delta® replacement parts. What You Must Do To Obtain Warranty Service or Replacement Parts. A warranty claim may be made and replacement parts may be obtained by calling 1 800 345 DELTA (3358) or by contacting us by mail or online as follows (please include your model number and date of original purchase): In the United States and Mexico: Delta Faucet Company Product Service 55 E. 111th Street Indianapolis, IN 46280 Attention: Customer Solutions www.deltafaucet.com/service-parts/contact-us In Canada: Masco Canada Limited, Plumbing Group Technical Service Centre 350 South Edgeware Road St. Thomas, Ontario, Canada N5P 4L1 Attention: Customer Service Proof of purchase (original sales receipt) from the original purchaser must be made available to Delta Faucet Company for all warranty claims unless the purchaser has registered the product with Delta Faucet Company or the product is a Delta® Recertified product purchased from deltafaucet.com. This warranty applies only to Delta® faucets manufactured after January 1, 2019 and installed in the United States of America, Canada and Mexico. Limitation on Duration of Implied Warranties. Please note that some states/provinces (including Quebec) do not allow limitations on how long an implied warranty lasts, so the below limitations may not apply to you. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, ANY IMPLIED WARRANTY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE, IS LIMITED TO THE STATUTORY PERIOD OR THE DURATION OF THIS WARRANTY, WHICHEVER IS SHORTER. Limitation of Special, Incidental or Consequential Damages. Please note that some states/provinces (including Quebec) do not allow the exclusion or limitation of special, incidental or consequential damages, so the below limitations and exclusions may not apply to you. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THIS WARRANTY DOES NOT COVER, AND DELTA FAUCET COMPANY SHALL NOT BE LIABLE FOR, ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LABOR CHARGES TO REPAIR, REPLACE, INSTALL OR REMOVE THIS PRODUCT), WHETHER ARISING OUT OF BREACH OF ANY EXPRESS OR IMPLIED WARRANTY, BREACH OF CONTRACT, TORT, OR OTHERWISE. DELTA FAUCET COMPANY SHALL NOT BE LIABLE FOR ANY DAMAGE TO THE FAUCET RESULTING FROM REASONABLE WEAR AND TEAR, OUTDOOR USE, MISUSE (INCLUDING USE OF THE PRODUCT FOR AN UNINTENDED APPLICATION), FREEZING WATER, ABUSE, NEGLECT OR IMPROPER OR INCORRECTLY PERFORMED INSTALLATION, MAINTENANCE OR REPAIR, INCLUDING FAILURE TO FOLLOW THE APPLICABLE INSTALLATION, CARE AND CLEANING INSTRUCTIONS. Notice to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. Additional Rights. This warranty gives you specific legal rights, and you may also have other rights which vary from state/province to state/province. This is Delta Faucet Company's exclusive written warranty and the warranty is not transferable. If you have any questions or concerns regarding our warranty, please contact us as provided above or view our Warranty FAQs at www.deltafaucet.com. Problem Solved, Once and for All A Classic Southern Dream Proud sponsor of the HGTV® Dream Home 2025 See Inside © 2024 Warner Bros. Discovery, Inc. or its subsidiaries and affiliates. All trademarks are the property of their respective owners. All rights reserved. Introducing Touch2O® with Touchless™ Technology A Kitchen That Keeps Up Create a space that works as hard as you do. LATEST RELEASES See What's New in 2025. Take a look at new Delta® products, all thoughtfully designed to make daily tasks easier and bring style into your favorite spaces. TECHNOLOGY INNOVATIONS The power is in your hands. Between jobs and kids and to-dos and errands, our hands are always full. That's why we created Touch2O® Technology, so you can turn on your faucet with just a tap and make life just a little bit easier.